
66240CBI

XENARC COOL BLUE INTENSE | Gas discharge headlight lamps for cars

Areas of application

- Headlight



Product benefits

- Exceptionally bright
- Offers high contrast
- Up to 20 % more light (compared to conventional coated gas discharge lamps)

Product features

- Blue effect without coating
- Color temperature: up to 5,500 K

Product datasheet

Technical data


Electrical data

Power input	35 W
Nominal wattage	35.00 W
Nominal voltage	85 V
Power input tolerance	±3 %
Test voltage	13.5 V

Photometrical data

Color temperature	4800 K
Luminous flux	3200 lm
Luminous flux tolerance	±15 %

Dimensions & weight



Length	77.0 mm
Diameter	9.0 mm
Product weight	16.00 g

Lifespan

Lifespan B3	1800 h
Lifespan Tc	2800 h

Additional product data

Base (standard designation)	P32d-2
-----------------------------	--------

Certificates & standards

ECE category	D2S ¹⁾
--------------	-------------------

¹⁾ To be operated only with approved electronic control gear

Product datasheet

Country specific categorizations

Order reference	66240CBI 35W P3
-----------------	-----------------

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321401359	OSRA66240CBI	-	-	-
4008321588883	OSRA66240CBIDUO	-	-	-

Product datasheet

Safety advice

XENARC lamp change is recommended to be carried out by a professional.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Volume	Gross weight
4008321401359	66240CBI	Folding carton box 1	33 mm x 33 mm x 87 mm	0.09 dm ³	25.07 g
4008321401366	66240CBI	Shipping carton box 10	78 mm x 97 mm x 186 mm	1.41 dm ³	307.87 g
4008321588883	66240CBI	Hard Cover Box 2	95 mm x 47 mm x 114 mm	0.51 dm ³	106.00 g
4008321588890	66240CBI	Shipping carton box 20	240 mm x 106 mm x 250 mm	6.36 dm ³	1279.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Legal advice

ECE approval

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.