

LUKOIL GENESIS SPECIAL VN 5W-30

Synthetic fuel economy low ash engine oil

APPROVALS

BMW LL-04
 MB-Approval 229.51
 Porsche C30
 VW 504 00/507 00

MEETS REQUIREMENTS

ACEA C3,
 ACEA A3/B4 and ACEA C2 suitable for use

PRODUCT DESCRIPTION

LUKOIL GENESIS SPECIAL VN 5W-30 is a synthetic fuel economy low ash engine oil perfectly suitable for engines especially with particulate filter or unit-injector system. It allows long maintenance intervals offers highest reliability. A new technology protects the environment as well as the particulate filter.

LUKOIL GENESIS SPECIAL VN 5W-30 offers the highest quality base oil maximum environmental protection and minimized, oil-related emissions. In addition, the lowSAPS formulation guarantees the least burden on the particulate filter. With the latest additive technology for maximum engine cleanliness, reduced friction of the moving parts, and long life of the engine is ensured. This moderne high performance low friction oil minimizes wear by rapid oil circulation, especially in the warm-up phase of the engine, allowing maximum loads and provides exceptionally high safety reserves. The oil also offers excellent low temperature properties, which ensures a quick start of the engine in extremely cold temperatures and long periods of use by the high profitability.

APPLICATION

LUKOIL GENESIS SPECIAL VN 5W-30 is used in Audi, BMW, Mercedes, Seat, Skoda, Volkswagen and many more.

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL GENESIS SPECIAL VN 5W-30
Density at 15 °C	kg/m ³	DIN 51575	851
Flash Point COC	°C	ISO 2592	230
Viscosity class	---	SAE J 300	5W-30
Viscosity at 40°C	mm ² /s	DIN 51562/T1	70.8
Viscosity at 100°C	mm ² /s	DIN 51562/T1	11.6
Pourpoint	°C	DIN ISO 3016	<-36

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

19 October 2015, Page 1/1

* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service Lubricants technics.lubes@lukoil.com

LUKOIL Lubricants Europe Oy +43(1)205 222-8800
 Ölhafen Lobau – Uferstr. 8
 1220 Vienna - Austria www.lukoil-lubricants.eu

member of::

